



TECHNICAL DATASHEET

WWW.JACOBI.NET



Jacobi
THE CARBON COMPANY

EcoSorb® GXB

extruded coal based
activated carbon

Features and Benefits

- High activity
- Extensive pore structure
- Exceptional hardness and strength
- Rigorously dedusted
- Optimum efficiency of operation
- High adsorption capacity, longer life
- Minimal product degradation giving low pressure drop
- Clean handling at adsorber loading and commissioning

Typical Applications

- Comfort air systems (HEVAC)
- De-oiling of compressed gas
- Biogas treatment (siloxane removal)
- Fresh air intake systems
- VOC removal

Available Pellet Diameters

- 0.9 mm
- 1.5 mm
- 2.0 mm
- 3.0 mm
- 4.0 mm
- 5.0 mm

Standard Packaging

- 25 kg bag (55 lb)
- 500 kg bulk bag (1100 lb)



The polyethylene valve bag from Jacobi sets the standard in the industry for clean, durable and safe handling.

EcoSorb® GXB is a high activity extruded activated carbon manufactured by steam activation from select grades of anthracite coal. This activated carbon is exceptionally hard and resistant to mechanical breakdown resulting from a unique binding and extrusion process used during manufacturing. EcoSorb® GXB has the perfect balance between adsorption and transport pores enabling the efficient adsorption of a range of organic contaminants present in air and gas streams with optimum capacity. As a result, it is particularly suited to the removal of organic compounds associated with industrial process streams and building ventilation systems.



Refiners and manufacturers rely upon EcoSorb® activated carbons for the efficient and economical treatment of vapour containing organics and other contaminants.

Specification

CTC activity	min. 60%
Moisture content (as packed)	max. 5%
Total ash content	max. 12%
Ball-pan hardness	min. 95%

Typical Properties

Butane activity	25%
Apparent density	470 - 530 kg/m ³
Pellet diameter tolerance	± 10%

* Specifications and typical properties are produced using Jacobi Carbons' test methods. They are listed for informational purposes only and not to be used as purchase specifications. Sales specifications can be obtained from your Jacobi Carbons Technical Sales Representative and should be reviewed before placing an order.

ECOGXB-DSE-B0803



Jacobi
THE CARBON COMPANY

CORPORATE OFFICE

Sweden

Jacobi Carbons AB
Bredbandet 1, Varvsholmen
SE-392 30 Kalmar

Tel: +46 480 417550
Fax: +46 480 417559
info@jacobi.net

EMEA

Germany

Jacobi Carbons GmbH
Feldbergstrasse 21
D-60323 Frankfurt/Main

Tel: +49 69 719107-0
Fax: +49 69 719107-20
info@jacobi.net

Finland

Jacobi Carbons AB (SS)
Ruoholahdenkatu 8
SF-00180 Helsinki

Tel: +358 9 643602
Fax: +358 9 642900
info@jacobi.net

Switzerland

Jacobi Carbons AG
Rheinweg 5
CH-8200 Schaffhausen

Tel: +41 52 647 30 00
Fax: +41 52 647 30 09
info@jacobi.net

United Kingdom

Jacobi Carbons Ltd.
Croft Court, Moss Estate
Leigh, Lancs, WN7 3PT

Tel: +44 1942 670 600
Fax: +44 1942 670 605
info@jacobi.net

www.jacobi.net

AMERICAS

United States

Jacobi Carbons, Inc.
1518 Walnut Street, 10th Floor
Philadelphia, PA 19102

Tel: (215) 546-3900
Fax: (215) 546-9921
info@jacobi.net

ASIA / PACIFIC

Sri Lanka

Jacobi Carbons Lanka (Pvt) Ltd.
618 Aluthmawatha Road
Colombo 15, Sri Lanka

Tel: +94 11 252 0364-5
Fax: +94 11 252 0366
info@jacobi.net

India

Jacobi Carbons India (Pvt) Ltd.
#122, First Floor, Bharathi Colony
Peelamedu, Coimbatore, 641004

Tel: +91 422 4397208
Fax: +91 422 4397209
info@jacobi.net

China

Jacobi Carbons Industry (Tianjin) Co. Ltd.
No. 31, 5th Coastal Way, TJPFTZ
Tanggu, Tianjin, 300456

Tel: +86 22 25763228
Fax: +86 22 25763228
info@jacobi.net

Malaysia

Jacobi Carbons (Asia) Sdn Bhd
Lot 12070-F, Jalan Usahajaya,
Kawasan Perusahaan Ringan Usahajaya,
14100 Permatang Tinggi, Bukit Mertajam, Penang

Tel: +604 588 2122
Fax: +604 588 6122
info@jacobi.net



Polyethylene valve bags,
20 bags per pallet.



Polypropylene liner-free
FIBCs (super sacks),
2 bags per pallet.

CAUTION Activated carbon is a strong oxidizing agent and can remove oxygen from air under wet or humid conditions. Care should be taken when entering confined spaces where wet activated carbon is present. Ensure the use of correct breathing apparatus. Material Safety Data Sheets should be consulted for further details on procedures in the event of contact with activated carbon.

NOTICE Due to the progressive nature of the Jacobi Carbons Group and the continually improving design and performance of our products, we reserve the right to change product specifications without prior notification. The information contained in this datasheet is intended to assist a customer in the evaluation and selection of products supplied by Jacobi Carbons. The customer is responsible for determining whether products and the information contained in this document are appropriate for customer's use. Jacobi Carbons assumes no obligation or liability for the usage of the information in this datasheet, no guarantees or warranties, expressed or implied, are provided. Jacobi Carbons disclaims responsibility and the user must accept full responsibility for performance of systems based on this data.

WORLDWIDE DISTRIBUTORS A diverse network of agents, strategically located around the world. Please contact any Jacobi Carbons office to locate your nearest distributor. AquaSorb®, EcoSorb®, GoldSorb®, ColorSorb®, DioxSorb®, AddSorb® and Jacobi are registered trademarks of Jacobi Carbons. © Jacobi Carbons, 2009.

ISO 9001
BUREAU VERITAS
Certification

